

# Quarter-Turn Pr14.1 L13.5

1-050



## Advantages

- IP65 to DIN EN 60529 by using sealing kit (optional).
- RH / LH application.
- Grounding by grounding nut or grounding clip.
- On request parts can be assembled.
- A pre-assembled quarter-turn can be installed in the cutout and combined with the finger pull of product system 1-060.

## Material

- **Housing:** zinc die, chrome plated or black or PA, black

## Remarks

With assembled cam - door thickness (S) max. 2mm

With unassambled cam - door thickness (S) max. 5mm

1. nut
2. grounding nut
3. grounding clip

When using finger pull (b) the H-dimension decreases by 0.8mm  
Please configure the quarter-turn with insert and cam.

## Quarter-Turn housing + nut

	Product number	Material	Surface	Grounding type	Installation type	Delivery Unit
a)	220-9001.00-00000	zinc die	chrome plated	-	screw-on	10 pcs.
a)	220-9002.00-00000	zinc die	chrome plated	Grounding nut	screw-on	10 pcs.
a)	220-9005.00-00000	zinc die	chrome plated	Grounding clip	screw-on	10 pcs.
a)	220-9003.00-00000	zinc die	black	-	screw-on	10 pcs.
a)	220-9004.00-00000	zinc die	black	Grounding nut	screw-on	10 pcs.
a)	220-9006.00-00000	zinc die	black	Grounding clip	screw-on	10 pcs.

---

	<b>Product number</b>	<b>Material</b>	<b>Surface</b>	<b>Grounding type</b>	<b>Installation type</b>	<b>Delivery Unit</b>
a)	220-9020.00-00000	PA	black	-	screw-on	10 pcs.
a)	220-9021.00-00000	PA	black	Grounding nut	screw-on	10 pcs.
a)	220-9022.00-00000	PA	black	Grounding clip	screw-on	10 pcs.

---



