

# Compression Latch Pr22.1 with Flap

1-075



## Advantages

- Compression 6mm.
- The open flap indicates locking position and protects against dust and water.
- The flap is standing upright (90°) in unlocked position.
- The spring-loaded flap first closes, when compression latch is closed securely.
- Seismic-proof according GR-63-CORE, Issue 4.
- Vibration-proof according to DIN EN 61373.
- IP65/IP67 according to DIN EN 60529.
- RH and LH version.
- Grounding by grounding nut.

## Material

- **Housing, flap and insert:** zinc die, black
- **Grounding nut:** zinc die, untreated
- **Screw:** steel, zinc plated
- **Nut and spring:** stainless steel
- **O-rings:** NBR

## Remarks

(S) Door-thickness max. 8mm

Please configure the quarter-turn with insert and cam.  
The H-dimension can be varied by the cranking of the cams.

1. stroke 6mm
2. o-ring
3. single-sided grounding nut



## Compression Latch with insert, version RH, closing left

	Product number	Insert	Installation type	Delivery Unit
a)	248-9601.00-00001	Double bit 3mm pin	screw-on	1 pc.
a)	248-9601.00-00002	Double bit 5mm pin	screw-on	1 pc.
a)	248-9601.00-00003	Square 8mm	screw-on	1 pc.
a)	248-9601.00-00004	Triangular 8mm	screw-on	1 pc.
a)	248-9601.00-00005	Conical square 9mm	screw-on	1 pc.

## Compression Latch with insert, version LH, closing right

	Product number	Insert	Installation type	Delivery Unit
a)	248-9651.00-00001	Double bit 3mm pin	screw-on	1 pc.
a)	248-9651.00-00002	Double bit 5mm pin	screw-on	1 pc.
a)	248-9651.00-00003	Square 8mm	screw-on	1 pc.
a)	248-9651.00-00004	Triangular 8mm	screw-on	1 pc.
a)	248-9651.00-00005	Conical square 9mm	screw-on	1 pc.

