

DST Quarter-Turn Pr32x20 L18

1-083DST



Advantages

- Flush quarter-turn for cutout 32x20mm.
- Rectangular cutout guarantees a perfect alignment.
- IP65 according to DIN EN 60529 (O-Ring for housing is included). O-Ring 200-1001.00-00000, for insert, please order separately.
- RH / LH application by rotatable bottom part.
- Grounding by grounding clip (optional)..
- On request parts can be pre-assembled
- The quarter-turn can be snapped-in as a completely pre-assembled unit.
- Installation tool-less and vibration-proof.
- Blind installation in closed profiles.

Material

- **Housing:** PA, black or zinc die, chrome plated
- **Snap wedges:** sintered steel
- **O-ring:** NBR, black

Remarks

Attention: H-dimension of the cam not less than 12mm!

Please configure the quarter-turn with insert and cam.

1. o-ring
2. rotatable bottom for RH/LH

Quarter-Turn

	Product number	Clamping range (S)	Material	Surface	Delivery Unit
a)	406-9005.00-00013	1 mm - 1.7 mm	PA	black	10 pcs.
a)	406-9005.00-00016	1.3 mm - 2 mm	PA	black	10 pcs.
a)	406-9005.00-00018	1.5 mm - 2.2 mm	PA	black	10 pcs.

	Product number	Clamping range (S)	Material	Surface	Delivery Unit
a)	406-9005.00-00021	1.8 mm - 2.5 mm	PA	black	10 pcs.
a)	406-9005.00-00026	2.3 mm - 3 mm	PA	black	10 pcs.
a)	406-9005.00-00031	2.8 mm - 3.5 mm	PA	black	10 pcs.
a)	406-9006.00-00013	1 mm - 1.7 mm	zinc die	chrome plated	10 pcs.
a)	406-9006.00-00016	1.3 mm - 2 mm	zinc die	chrome plated	10 pcs.
a)	406-9006.00-00018	1.5 mm - 2.2 mm	zinc die	chrome plated	10 pcs.
a)	406-9006.00-00021	1.8 mm - 2.5 mm	zinc die	chrome plated	10 pcs.
a)	406-9006.00-00026	2.3 mm - 3 mm	zinc die	chrome plated	10 pcs.
a)	406-9006.00-00031	2.8 mm - 3.5 mm	zinc die	chrome plated	10 pcs.

