

# Safety Quarter-Turn Pr20.1 L18

1-085.01



## Advantages

- Flush safety quarter-turn for cutout Pr20.1.
- Completely closed housing surface.
- Vibration-proof according to DIN EN 61373 also at high sealing pressure, by built-in spring loaded link.
- IP65 according to DIN EN 60529.
- RH / LH application.
- Grounding by single-sided grounding nut.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.



## Material

- **Housing, insert and spring loaded link:** zinc die, matte chrome plated
- **O-ring and flat external seal:** NBR Perbunan, black
- **Nut and grounding nut:** zinc die, untreated
- **Serrated lock washer:** steel, zinc plated

## Remarks

(S) Door-thickness max. 8mm

Completely pre-assembled **without** cam.

1. spring loaded link
2. housing
3. serrated lock washer
4. flush, closed surface

## Safety quarter-turn with insert

	Product number	Version	Insert	Installation type	Delivery Unit
a)	255-9812.00-00000	with serrated lock washer	Conical square 9mm	screw-on	10 pcs.
b)	255-9813.00-00000		Square 8mm	screw-on	10 pcs.
c)	255-9814.00-00000		Triangular 8mm	screw-on	10 pcs.

