

DST Quarter-Turn Polyamide PrA L18

1-100DST



Advantages

- For cutout PrA.
- Rectangular cutout guarantees a perfect alignment.
- IP65 according to DIN EN 60529.
For IP65 according to DIN EN 60529 o-ring (200-1001.00-00000) for insert (optional).
- RH / LH application by rotatable bottom part.
- Grounding by grounding clip.
- Also a 3-point cam can be pre-assembled.
- The Quarter-turn can be snapped-in as a completely pre-assembled unit.
- Installation tool-less and vibration-proof.
- Blind installation in closed profiles.

Material

- **Housing:** PA, black
- **Bottom:** zinc die, zinc plated
- **Snap wedges:** sintered steel, zinc plated
- **Grounding clip:** stainless steel
- **O-ring:** NBR, black

Remarks

Attention: H-dimension of the cam not less than 16mm (5/8).

Please configure the Quarter-turn with insert and cam.

With escutcheons, this Quarter-turn can also be used for cutouts PrB and PrC (see product system 3-136).

1. rotatable bottom for RH/LH
2. o-ring

Quarter-turn, PA

	Product number	Clamping range (S)	Grounding type	Installation type	Delivery Unit
a)	408-9301.00-00015	0.8 mm - 1.5 mm	Grounding clip	tool-less	10 pcs.
a)	408-9301.00-00020	1.3 mm - 2 mm	Grounding clip	tool-less	10 pcs.
a)	408-9301.00-00025	1.8 mm - 2.5 mm	Grounding clip	tool-less	10 pcs.
a)	408-9301.00-00030	2.3 mm - 3 mm	Grounding clip	tool-less	10 pcs.
a)	408-9301.00-00035	2.8 mm - 3.5 mm	Grounding clip	tool-less	10 pcs.

	Product number	Clamping range (S)	Grounding type	Installation type	Delivery Unit
a)	408-9302.00-00015	0.8 mm - 1.5 mm	-	tool-less	10 pcs.
a)	408-9302.00-00020	1.3 mm - 2 mm	-	tool-less	10 pcs.
a)	408-9302.00-00025	1.8 mm - 2.5 mm	-	tool-less	10 pcs.
a)	408-9302.00-00030	2.3 mm - 3 mm	-	tool-less	10 pcs.
a)	408-9302.00-00035	2.8 mm - 3.5 mm	-	tool-less	10 pcs.

