

Cylinder Quarter-Turn Pr20.1 L18 Stainless Steel

7-084



Advantages

- For cutout 20.1.
- Grounding by grounding nut.
- **Version a)**
- RH / LH application.
- For stability the cam is secured by a nut DIN 934.
- **Version b)**
- RH and LH version.
- To insure it turns freely, the slam-cam is secured by a shoulder screw.

Material

- **Housing, grounding nut, adapter and hexagon nut:** AISI 316
- **Spring washer:** AISI 301
- **Cylinder barrel:** stainless steel

Remarks

- (S) Door-thickness max. 8mm
- IP65 according to DIN EN 60529 only **with** dustcap, see product system 1-270.
1. mounting position of the spring washer

Cylinder quarter-turn

	Product number	Latching type	Installation type	Delivery Unit
a)	200-9232.00-00000	keyed alike DIRAK 1333	screw-on	1 pc.
a)	200-9233.00-00000	keyed different	screw-on	1 pc.

Cylinder quarter-turn with slam cam

	Product number	Latching type	Version	Installation type	Delivery Unit
b)	200-9236.00-01333	keyed alike DIRAK 1333	RH version	screw-on	1 pc.
b)	200-9236.00-99999	keyed different	RH version	screw-on	1 pc.
b)	200-9237.00-01333	keyed alike DIRAK 1333	LH version	screw-on	1 pc.
b)	200-9237.00-99999	keyed different	LH version	screw-on	1 pc.

