

Compression Latch Pr20.1 with Wing Knob or Round Knob Stainless Steel

7-089



Advantages

- Compression 6mm.
- Marking on the housing head open/closed in the form of a padlock, is differentiated by color.
- Insert with viewing window.
- Vibration-proof.
- IP65/67 according to DIN EN 60529.
- RH and LH version.
- Grounding by single-sided grounding nut.
- The H-dimension can be varied via the cranking of the cams.
- The cam can be varied via H-dimension adjustment on the threaded square rod.

Material

- **Housing, insert, knurled wheel, threaded square rod and grounding nut:** AISI 316
- **Catch:** AISI 301

Remarks

(S) Door-thickness max. 12mm for GL22

1. compression 6mm
2. single-sided grounding nut
3. flat external seal
4. catch with knurled wheel
5. viewing window

Compression Latch, version RH, closing left

	Product number	Insert	Version	Installation type	Delivery Unit
a)	248-9050.01-00001	Wing knob	long axis	screw-on	1 pc.
a1)	248-9048.01-00001	Wing knob	short axis	screw-on	1 pc.
b)	248-9050.01-00002	Round knob	long axis	screw-on	1 pc.
b1)	248-9048.01-00002	Round knob	short axis	screw-on	1 pc.

Compression Latch, version LH, closing right

	Product number	Insert	Version	Installation type	Delivery Unit
a)	248-9050.02-00001	Wing knob	long axis	screw-on	1 pc.
a1)	248-9048.02-00001	Wing knob	short axis	screw-on	1 pc.
b)	248-9050.02-00002	Round knob	long axis	screw-on	1 pc.
b1)	248-9048.02-00002	Round knob	short axis	screw-on	1 pc.

