

# Swinghandle RS PrC f. iLOQ Half Cylinder D50S

2-090.05



## Advantages

- Swinghandle with liftable operating lever.
- Suitable for iLOQ half cylinder D50S.511SD and D50S.531.SD.
- 90° Closing rotation.
- IP65 according to DIN EN 60529.
- RH / LH application.
- Bearing plate with seal for Cutout 150x25.
- Grounding by grounding clip (optional).

## Material

**Swinghandle and dish:** zinc die, black

**Shaft:** brass

**Bearing plate:** PrC = zinc die, untreated  
150x25 = Aluminum, untreated

**Cap:** PA, black

**Seals:** NBR

## Remarks

(S) Door-thickness 1.5 - 2.5mm

1. Holding for sensor (sensor not in scope of delivery)
2. Bearing plate 150x25
3. Bearing plate PrC
4. Cylinder iLOQ is not included in the scope of delivery. Available at [www.iloq.com](http://www.iloq.com)

## Swinghandle for iLOQ D50S

	Product number	Version	Installation type	Delivery Unit
a)	207-9146.00-00000	Bearing plate PrC	screw-on	1 pc.



---

	<b>Product number</b>	<b>Version</b>	<b>Installation type</b>	<b>Delivery Unit</b>
b)	207-9147.00-00000	Bearing plate 150x25	screw-on	1 pc.

---

