

Swinghandle RS 130 for Rod Latch PrA

2-110



Advantages

- Swinghandle for cutout 130.
- For sheet metal and plastic enclosures.
- 135° rotation.
- The polyamide handle is fully insulated.
- The swinghandle can be locked with profile-cylinders with 45° or 90° cylinder cam feature.
- IP65 according to DIN EN 60529.
- RH / LH application.
- By using the lock support d), the assembly of the rod latch PrA is possible.

Material

- **Handle:** zinc die, black or PA, black
- **Dish and cap:** PA, black
- **Lock support:** zinc die, untreated

Remarks

(S) Door-thickness max. 3mm

For doors to be symmetrical for RH and LH operations, two cutouts □46mm with lock support e) are required.

Profile half cylinders and their assembly must be ordered separately.



Swinghandle for profile cylinder

Product number	Latching type	Handle material	Cylinder cover material	Securable	Reinforced dustcover	Internal cover	Installation type	Delivery Unit
a) 207-9023.00-00000	PHZ 40mm	PA	-	-	-	Ø46	screw-on	1 pc.

Product number	Latchingtype	Handlematerial	Cylinder covermaterial	Securable	Reinforceddustcover	Internalcover	Installationtype	DeliveryUnit
a) 207-9024.00-00000	PHZ 40mm	PA	PA	Yes	-	Ø46	screw-on	1 pc.
b) 207-9030.00-00000	PHZ 45mm	PA	PA	Yes	-	Ø46	screw-on	1 pc.
b) 207-9034.00-00000	PHZ 45mm	zinc die	PA	Yes	-	Ø46	screw-on	1 pc.
c) 207-9346.00-00000	PHZ 45mm	zinc die	PA	Yes	Yes	□46	screw-on	1 pc.

Lock support

Product number	Version	Delivery Unit
d) 207-3501.00-00000	for cutout Ø22.5	1 pc.
e) 207-2706.00-00000	for cutout □46	1 pc.

