

# Concealed Hinge Pr03 120°

4-120



## Advantages

- For surface mounted doors.
- Hinge concealed.
- Door bending 18 mm.
- RH / LH application.
- 120° Opening angle.
- Frame-part weld-on or screw-on.

## Material

- **Frame-part:** steel, zinc plated or steel, untreated
- **Door-part:** steel, untreated
- **Pins and retaining ring:** steel, zinc plated
- **O-ring:** NBR

## Remarks



## Concealed hinge

	Product number	Version	Surface frame-part	Pin version	Installation type frame-part	Delivery Unit
a)	216-9001.00-00000		untreated	without groove	weld-on	10 pcs.
b)	216-9009.00-00000		untreated	with groove incl. locking washer DIN6799	weld-on	10 pcs.
c)	216-9009.00-00001		untreated	with groove incl. o-ring	weld-on	10 pcs.
d)	216-9020.00-00000	reinforced	untreated	without groove	weld-on	10 pcs.

---

	Product number	Version	Surface frame-part	Pin version	Installation type frame-part	Delivery Unit
e)	216-9018.00-00000	reinforced	zinc plated	with groove incl. locking washer DIN6799	weld-on	10 pcs.
f)	216-9018.00-00001	reinforced	zinc plated	with groove incl. o-ring	weld-on	10 pcs.
g)	216-9002.00-00000		zinc plated	without groove	screw-on	10 pcs.
h)	216-9010.00-00000		untreated	with groove incl. locking washer DIN6799	screw-on	10 pcs.
i)	216-9010.00-00001		untreated	with groove incl. o-ring	screw-on	10 pcs.
j)	216-9021.00-00000	reinforced	zinc plated	without groove	screw-on	10 pcs.
k)	216-9019.00-00000	reinforced	zinc plated	with groove incl. locking washer DIN6799	screw-on	10 pcs.
l)	216-9019.00-00001	reinforced	zinc plated	with groove incl. o-ring	screw-on	10 pcs.

---

