

Concealed Hinge Pr03 120°

4-124



Advantages

- For surface mounted doors.
- Hinge concealed.
- Door bending 23mm.
- RH / LH application.
- 120° Opening angle.
- Door-part weld-on.

Material

- **Frame-part, pin and fastening washer:** steel, zinc plated
- **Door-part:** steel, untreated

Remarks

1. installation instruction for fastening washer



Concealed hinge

	Product number	Frame-part	cutout in frame	Pin version	Delivery Unit
a)	243-9103.00-00000	with countersunk holes for M6	Ø6.3 or M6	without groove	10 pcs.
b)	243-9104.00-00000	with countersunk holes for M6	Ø6.3 or M6	with groove incl. locking washer DIN6799	10 pcs.

	Product number	Frame-part	cutout in frame	Pin version	Delivery Unit
c)	243-9104.00-00001	with countersunk holes for M6	Ø6.3 or M6	with groove incl. o-ring	10 pcs.
d)	243-9101.00-00000	with countersunk holes for M6 + fastening washer	□8 or Ø10	without groove	10 pcs.
e)	243-9102.00-00000	with countersunk holes for M6 + fastening washer	□8 or Ø10	with groove incl. locking washer DIN6799	10 pcs.
f)	243-9102.00-00001	with countersunk holes for M6 + fastening washer	□8 or Ø10	with groove incl. o-ring	10 pcs.
g)	243-9109.00-00000	with studs for M6 + fastening washer	Ø6.3, □8, Ø10	without groove	10 pcs.
h)	243-9110.00-00000	with studs for M6 + fastening washer	Ø6.3, □8, Ø10	with groove incl. locking washer DIN6799	10 pcs.
i)	243-9110.00-00001	with studs for M6 + fastening washer	Ø6.3, □8, Ø10	with groove incl. o-ring	10 pcs.

