

# DST Hinge 40x40 Pr01 180°

4-250DST



## Advantages

- Hinge with DIRAK-SNAP-Technology.
- For nested doors.
- Hinge visible.
- RH / LH application.
- 180° Opening angle.
- Installation tool-less or tool-less / screw-on.

## Material

- **Hinge halves:** zinc die, black
- **Pin:** stainless steel
- **Snap wedges:** sintered steel, zinc plated

## Remarks

Other data and dimensions see product system 4-250.

## Hinge

	Product number	Version	Clamping range (S)	Pin version	Installation type	Delivery Unit
a)	418-9001.00-00015	clip-in	1.2 mm - 1.7 mm	pressed in	tool-less	10 pcs.
a)	418-9001.00-00020	clip-in	1.7 mm - 2.2 mm	pressed in	tool-less	10 pcs.
a)	418-9001.00-00025	clip-in	2.2 mm - 2.7 mm	pressed in	tool-less	10 pcs.
a)	418-9001.00-00030	clip-in	2.7 mm - 3.2 mm	pressed in	tool-less	10 pcs.
b)	418-9002.00-00015	with molded in countersunk screws M5	1.2 mm - 1.7 mm	pressed in	tool-less / screw-on	10 pcs.
b)	418-9002.00-00020	with molded in countersunk screws M5	1.7 mm - 2.2 mm	pressed in	tool-less / screw-on	10 pcs.
b)	418-9002.00-00025	with molded in countersunk screws M5	2.2 mm - 2.7 mm	pressed in	tool-less / screw-on	10 pcs.
b)	418-9002.00-00030	with molded in countersunk screws M5	2.7 mm - 3.2 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9003.00-00015	with countersunk holes for M5	1.2 mm - 1.7 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9003.00-00020	with countersunk holes for M5	1.7 mm - 2.2 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9003.00-00025	with countersunk holes for M5	2.2 mm - 2.7 mm	pressed in	tool-less / screw-on	10 pcs.

---

	Product number	Version	Clamping range (S)	Pin version	Installation type	Delivery Unit
c)	418-9003.00-00030	with countersunk holes for M5	2.7 mm - 3.2 mm	pressed in	tool-less / screw-on	10 pcs.

---

