

DST Captive Fastener □9.5

1-035DST



Advantages

- With DIRAK-SNAP-Technology for joining of flat metal sheets and securely latching doors and covers.
- For cutout □9.5.
- Meets machinery directive 2006/42EC.
- After pre-assembly the concern of losing, dropping or misplacing hardware is eliminated.
- Held securely in the cutout.
- Seismic-proof according to GR-63-CORE, Issue 4.
- Vibration-proof according to DIN EN 61373.
- Operation by handwheel / Phillips H2 or Torx 15.
- Opening by a ¼ turn of the insert.
- One-piece.

Material

- **Housing:** zinc die, matt chrome plated or black
- **Insert:** zinc die, zinc plated
- **Springs:** spring steel
- **Snap wedges:** sintered steel, zinc plated

Remarks

Removal: turning the screwdriver counterclockwise draws back the SNAP wedges (3.). The leaf spring (1.) pushes the Fastener out of the rear panel, but it remains captive in the front panel, held by the U-shaped spring (2.). (4.) Cutout in the rear panel can also be an ablong hole for tolerance adjustment. (5.) Cutout front panel. The (S) dimension indicates the total thickness of the sheet metal panels.



Fastener, zinc die

Product number	Surface	Clamping range (S)	Insert	Installation type	Delivery Unit
a) 294-9210.00-00017	chrome plated	1.5 mm - 2 mm	Turning knob/Phillips H2	tool-less	10 pcs.
a) 294-9210.00-00026	chrome plated	2.5 mm - 2.8 mm	Turning knob/Phillips H2	tool-less	10 pcs.
a) 294-9210.00-00034	chrome plated	3.3 mm - 3.6 mm	Turning knob/Phillips H2	tool-less	10 pcs.
a) 294-9210.00-00042	chrome plated	4.1 mm - 4.4 mm	Turning knob/Phillips H2	tool-less	10 pcs.
a) 294-9211.00-00017	black	1.5 mm - 2 mm	Turning knob/Phillips H2	tool-less	10 pcs.
a) 294-9211.00-00026	black	2.5 mm - 2.8 mm	Turning knob/Phillips H2	tool-less	10 pcs.
a) 294-9211.00-00034	black	3.3 mm - 3.6 mm	Turning knob/Phillips H2	tool-less	10 pcs.
a) 294-9211.00-00042	black	4.1 mm - 4.4 mm	Turning knob/Phillips H2	tool-less	10 pcs.

	Product number	Surface	Clamping range (S)	Insert	Installation type	Delivery Unit
b)	294-9220.00-00138	black	3.7 mm - 4 mm	Torx insert	tool-less	10 pcs.

