

DST Fastener 8x15

1-040DST



Advantages

- With DIRAK-SNAP-Technology for joining metal sheets.
- For cutout 8x15.
- Vibration-proof.
- Tool-less installation.
- The joining of metal sheets is achieved by pressing the fastener into the cutouts.
- With tool Part-No.: 292-0302.70 this fastener can be disconnected both from inside (after removal of the red plug) and from the outside.
- The tool is captive in the open position.

Material

- **Housing:** PA, black or light grey, RAL 7035
- **Snap wedges:** Grivory, black

Remarks

1. installation
2. disassembly
3. disassemble red plug

The dimension (S) always means the thickness of both sheets e.g.:

$$1.5 + 1.5 = 3$$

$$2.0 + 1.0 = 3$$

$$2.0 + 2.0 = 4$$

Fastener, PA

Product number	Surface	Clamping range (S)	Installation type	Delivery Unit
294-9001.00-00015	black	1.5 mm - 1.8 mm	tool-less	10 pcs.
294-9001.00-00020	black	2 mm - 2.3 mm	tool-less	10 pcs.
294-9001.00-00030	black	3 mm - 3.3 mm	tool-less	10 pcs.

Product number	Surface	Clamping range (S)	Installation type	Delivery Unit
294-9001.00-00040	black	4 mm - 4.3 mm	tool-less	10 pcs.
294-9002.00-00015	light grey RAL 7035	1.5 mm - 1.8 mm	tool-less	10 pcs.
294-9002.00-00020	light grey RAL 7035	2 mm - 2.3 mm	tool-less	10 pcs.
294-9002.00-00030	light grey RAL 7035	3 mm - 3.3 mm	tool-less	10 pcs.
294-9002.00-00040	light grey RAL 7035	4 mm - 4.3 mm	tool-less	10 pcs.

