


Tenon Blocks and Anti-twist Protection

4-248

RoHS
WEEE

Advantages

- For application with hinges 4-247 and 4-247.01.
- Tenon blocks for 8 or 10mm groove.
- Fastening by M6.
- Anti-twist protection for sheet metal construction.
- For vertical or horizontal applications.
- Tolerance compensation possible by oblong holes.

Material

- **Tenon blocks and anti-twist protection:** zinc die, untreated

Remarks

Tenon Blocks and Anti-twist Protection

	Product number	Name	Groove width	Cutout	Thread size	Door-thickness (S)	Delivery Unit
a)	265-1001.00-00000	Tenon blocks with anti-twist protection	8 mm	8 x 20 to 25 mm	M6	0 mm - 3.2 mm	10 pcs.
b)	265-1002.00-00000	Tenon blocks with anti-twist protection	10 mm	10 x 20 to 25 mm	M6	0 mm - 3.2 mm	10 pcs.
c)	265-1101.00-00000	Anti-twist protection for square	8 mm	8 x 20 to 25 mm			10 pcs.
d)	265-1102.00-00000	Anti-twist protection for square	10 mm	10 x 20 to 25 mm			10 pcs.
e)	265-1103.00-00000	Anti-twist protection for drill-holes		3 options, see drawing			10 pcs.

