

# Eject and Turn T-Handle FS/RS

3-145



## Advantages

- T-handle with 90° swing-out and 135° rotatable T-handle element.
- For flat or round rods.
- Safety tested according to RC2 DIN 1630.  
Only in combination with profile half cylinders according to DIN 18252.
- Very tight tolerances.
- The flat design prevents the handle from being used as a climbing aid.
- The locking cylinder can not be forced inwards by axial forces.
- The T-handle can not be folded down if not in line with the housing.
- Separate locking device sub-unit. Suitable for: Euro cylinder, KABA cylinder and padlock.
- Application inside or outside the sealed area.
- IP65 according to DIN EN 60529.
- RH / LH application.
- Condensation water drain.



## Material

- **Dish, T-handle:** zinc die, black
- **Flat rod and rod stub:** steel, zinc plated
- **Padlock bolt:** AISI 303
- **O-ring:** NBR, black

## Remarks

(S) Door-thickness 1.5 - 2.5mm

1. stroke 24mm [0.945]
2. position of the spacer if used outside the sealed area
3. position of the spacer if used inside the sealed area
4. closed and locked
5. open cover
6. turn key: T-handle ejects
7. T-handle can be operated

Profile half cylinders and their assembly must be ordered separately.

Version with insert on request.

## T-handle with cylinder cover

	Product number	Latching type	Padlock	Installation type	Delivery Unit
a)	302-9001.00-60000	PHZ 40mm	-	screw-on	1 pc.

---

	Product number	Latching type	Padlock	Installation type	Delivery Unit
b)	302-9001.00-30000	PHZ 40mm	Yes	screw-on	1 pc.
c)	302-9001.00-50000	KABA	-	screw-on	1 pc.
d)	302-9001.00-20000	KABA	Yes	screw-on	1 pc.

---



