

Swinghandle FS PrC for Insert

3-150.03



Advantages

- The locking cam is included.
- Version with cylinder cover is securable with wire padlock.
- IP65 according to DIN EN 60529 - version dish with cap.
- Dish with hook version is secured outside the sealed area.
- RH / LH application.
- Grounding by grounding clip (optional).

Material

- **Swinghandle:** zinc die, chrome plated or black or PA, black
- **Dish:** PA, black

Remarks

(S) Door-thickness 1.5 - 2.5mm

The swinghandles can be retrofitted with sliding cap product system 2-091.

Inserts and their assembly must be ordered separately.



Swinghandle, dish PA, for insert

Product number	Handle material	Surface handle	Dish	IP protection	Cylinder cover material	Installation type	Delivery Unit
a) 107-9247.00-00000	zinc die	chrome plated	with cap	IP65		screw-on	1 pc.
a) 107-9246.00-00000	zinc die	black	with cap	IP65		screw-on	1 pc.
b) 107-9251.00-00000	zinc die	chrome plated	with hook			screw-on	1 pc.
b) 107-9250.00-00000	zinc die	black	with hook			screw-on	1 pc.
a) 207-9270.00-00000	PA	black	with cap	IP65		screw-on	1 pc.
a) 207-9271.00-00000	PA	black	with cap	IP65	PA	screw-on	1 pc.
b) 207-9272.00-00000	PA	black	with hook			screw-on	1 pc.
b) 207-9273.00-00000	PA	black	with hook		PA	screw-on	1 pc.

