

Swinghandle FS PrC for KABA-/ Assa-Cylinder

3-150.05



Advantages

- Swinghandle a) with Ø22mm for KABA 8-cylinder.
- Swinghandle b) with oblong hole 35x20mm for Assa-, Abloy-, TrioVing-cylinder. Suitable for 5- or 7-piston cylinder. Locking cam, adapter and fitting material is included for both versions.
- Version with cylinder cover is securable with wire padlock.
- IP65 according to DIN EN 60529.
- RH / LH application.
- Grounding by grounding clip (optional).

Material

- **Swinghandle and dish:** PA, black

Remarks

(S) Door-thickness 1.5 - 2.5mm

Swinghandle PA, dish with cap

	Product number	Latching type	Cylinder cover material	Securable	Installation type	Delivery Unit
a)	207-9214.00-00000	KABA-cylinder			screw-on	1 pc.
a)	207-9215.00-00000	KABA-cylinder	PA	Yes	screw-on	1 pc.
b)	207-9218.00-00000	Assa / Abloy / TrioVing			screw-on	1 pc.
b)	207-9219.00-00000	Assa / Abloy / TrioVing	PA	Yes	screw-on	1 pc.
b)	207-9220.00-00000	Assa / Abloy / TrioVing	PA, reinforced	Yes	screw-on	1 pc.

