

# Swinghandle FS PrC f. iLOQ Half Cylinder D50S

3-150.06



## Advantages

- Swinghandle with liftable operating lever.
- Suitable for iLOQ S50 half cylinder D50S.511.SD and D50S.531.SD.
- 90° Closing rotation.
- IP65 according to DIN EN 60529.
- RH / LH application, or RH and LH version.
- Grounding by grounding clip (optional).

## Material

**Swinghandle and dish:** zinc die, black

**Shaft:** brass

**Cap with sealing for rod latch cutout 150x25:** aluminum, untreated

**Cap:** PA, black

**Seals:** NBR

## Remarks

(S) Door-thickness 1,5 - 2,5mm

1. Holding for sensor (sensor not in scope of delivery)
2. Cap with rod latch 150x25
3. Rod latch
4. Cylinder iLOQ is not included in the scope of delivery. Available at [www.iloq.com](http://www.iloq.com)

## Swinghandle for iLOQ D50S

	Product number	Version	Cutout	Installation type	Delivery Unit
a)	207-9148.00-00000	RH / LH application	PrC	screw-on	1 pc.
b)	207-9149.00-000LH	LH version	150 x 25	screw-on	1 pc.
b)	207-9149.00-000RH	RH version	150 x 25	screw-on	1 pc.

