

# DST Swinghandle FS PrC for PHZ

3-150DST



## Advantages

- Swinghandle for profile-cylinder to DIN 18252.
- Tool-less installation.
- Installation with internal caps and o-ring for IP65 EN 60529 (seals are included).
- The swinghandle is symmetric and can be applied both for RH and LH doors.
- The swinghandle pre-assembled by DIRAK is hooked into the cutout provided and then clipped into place in the upper area.
- The flat rods are placed into shown position and secured by the clip-on PA cover.

## Material

- **Swinghandle and dish:** PA, black
- **Snap wedges and pinion:** sintered steel

## Remarks

Suitable flat rods see product system 3-171DST.

1. stroke 24mm
2. clearance height
3. hook-in the lower part and snap-in the swinghandle
4. LH, clockwise opening door
5. RH, counterclockwise opening door
6. clip cover

Profile half cylinders and their assembly must be ordered separately.

## Swinghandle PA for PHZ 40mm

	Product number	Clamping range (S)	Dish	IP protection	Cylinder cover	Installation type	Delivery Unit
a)	407-9501.00-00015	1.3 mm - 2 mm	with hook and cap	IP65	-	tool-less	1 pc.
a)	407-9501.00-00018	1.5 mm - 2.2 mm	with hook and cap	IP65	-	tool-less	1 pc.

---

	Product number	Clamping range (S)	Dish	IP protection	Cylinder cover	Installation type	Delivery Unit
a)	407-9501.00-00020	1.8 mm - 2.5 mm	with hook and cap	IP65	-	tool-less	1 pc.
a1)	407-9502.00-00015	1.3 mm - 2 mm	with hook and cap	IP65	Yes	tool-less	1 pc.
a1)	407-9502.00-00018	1.5 mm - 2.2 mm	with hook and cap	IP65	Yes	tool-less	1 pc.
a1)	407-9502.00-00020	1.8 mm - 2.5 mm	with hook and cap	IP65	Yes	tool-less	1 pc.
b)	407-9504.00-00015	1.3 mm - 2 mm	with hook		-	tool-less	1 pc.
b)	407-9504.00-00018	1.5 mm - 2.2 mm	with hook		-	tool-less	1 pc.
b)	407-9504.00-00020	1.8 mm - 2.5 mm	with hook		-	tool-less	1 pc.
b1)	407-9503.00-00015	1.3 mm - 2 mm	with hook		Yes	tool-less	1 pc.
b1)	407-9503.00-00018	1.5 mm - 2.2 mm	with hook		Yes	tool-less	1 pc.
b1)	407-9503.00-00020	1.8 mm - 2.5 mm	with hook		Yes	tool-less	1 pc.

---

