

Snap-Lock Pr20.1

1-501



Advantages

- **Version a):** the spring loaded cam is operated by the key.
- **Version b):** the spring loaded cam is operated by a lockable push-button.
- **Version c):** the spring loaded cam is operated by a push-button.
- All locks supplied with two keys.
- Grounding by single-sided grounding nut.

Material

- **Snap-Lock:** zinc die, chrome plated
- **Grounding Nut:** zinc die

Remarks

By using a finger pull the dimensions (S) and H decreases by **2mm!**

1. black coating

Snap-Lock

| | Product number | Latching type | Housing length | H-dimension | Door-thickness (S) | Delivery Unit |
|----|-------------------|-------------------------|----------------|-------------|--------------------|---------------|
| a) | 264-9001.00-00000 | keyed different | 31,5 mm | 20 mm | 10 mm - 10 mm | 1 pc. |
| a) | 264-9002.00-00000 | keyed alike DIRAK D0205 | 31,5 mm | 20 mm | 10 mm - 10 mm | 1 pc. |
| a) | 264-9003.00-00000 | keyed different | 36,5 mm | 25 mm | 15 mm - 15 mm | 1 pc. |
| a) | 264-9004.00-00000 | keyed alike DIRAK D0205 | 36,5 mm | 25 mm | 15 mm - 15 mm | 1 pc. |
| b) | 264-9005.00-00000 | keyed different | 31,5 mm | 20 mm | 10 mm - 10 mm | 1 pc. |
| b) | 264-9006.00-00000 | keyed alike DIRAK D0205 | 31,5 mm | 20 mm | 10 mm - 10 mm | 1 pc. |
| b) | 264-9007.00-00000 | keyed different | 36,5 mm | 25 mm | 15 mm - 15 mm | 1 pc. |
| b) | 264-9008.00-00000 | keyed alike DIRAK D0205 | 36,5 mm | 25 mm | 15 mm - 15 mm | 1 pc. |
| c) | 264-9009.00-00000 | Push button | 31,5 mm | 20 mm | 10 mm - 10 mm | 1 pc. |

