

# DST Bridge Handle OMICRON

6-1133DST



## Advantages

- Elegant bridge handle with DIRAK-SNAP-Technology in different lengths.
- This handle is suitable for the computer industry, 19" technology, enclosures, equipments and other applications.
- Tool-less installation.

## Material

- **Bridge handle:** zinc die, matte chrome plated
- **Other surfaces on request.**
- **Snap wedges:** sintered steel

## Remarks

## Quarter-turn, PA

Product number	Clamping range (S)	L	L1	L2	Installation type	Delivery Unit
413-9013.40-00609	0.6 mm - 0.9 mm	39,3 mm	55 mm	43 mm	tool-less	10 pcs.
413-9013.40-00811	0.8 mm - 1.1 mm	39,3 mm	55 mm	43 mm	tool-less	10 pcs.
413-9013.40-01215	1.2 mm - 1.5 mm	39,3 mm	55 mm	43 mm	tool-less	10 pcs.
413-9013.40-01821	1.8 mm - 2.1 mm	39,3 mm	55 mm	43 mm	tool-less	10 pcs.
413-9013.40-02225	2.2 mm - 2.5 mm	39,3 mm	55 mm	43 mm	tool-less	10 pcs.
413-9014.40-00609	0.6 mm - 0.9 mm	64,3 mm	80 mm	68 mm	tool-less	10 pcs.
413-9014.40-00811	0.8 mm - 1.1 mm	64,3 mm	80 mm	68 mm	tool-less	10 pcs.
413-9014.40-01215	1.2 mm - 1.5 mm	64,3 mm	80 mm	68 mm	tool-less	10 pcs.
413-9014.40-01821	1.8 mm - 2.1 mm	64,3 mm	80 mm	68 mm	tool-less	10 pcs.
413-9014.40-02225	2.2 mm - 2.5 mm	64,3 mm	80 mm	68 mm	tool-less	10 pcs.
413-9015.40-00609	0.6 mm - 0.9 mm	89,3 mm	105 mm	93 mm	tool-less	10 pcs.
413-9015.40-00811	0.8 mm - 1.1 mm	89,3 mm	105 mm	93 mm	tool-less	10 pcs.
413-9015.40-01215	1.2 mm - 1.5 mm	89,3 mm	105 mm	93 mm	tool-less	10 pcs.
413-9015.40-01821	1.8 mm - 2.1 mm	89,3 mm	105 mm	93 mm	tool-less	10 pcs.

---

Product number	Clamping range (S)	L	L1	L2	Installation type	Delivery Unit
413-9015.40-02225	2.2 mm - 2.5 mm	89,3 mm	105 mm	93 mm	tool-less	10 pcs.

---

