

Hinged Recessed Handle, flush mounted

6-1380



Advantages

- Vibration-proof, rattle-free construction.
- To use in special areas such as road vehicles and railcars/wagons.
- Prevents accumulation of dirt due to the completely closed housing surface.
- **Variant a)** with lock and opening angle about 60° or 80°.
- Integrated safety quarter-turn \square 8.
- Operation of the hinged recess handle only possible with an insert key.
- **Variant b)** without lock and opening angle about 60° or 80°.

Material

- **Hinged recessed handle:** zinc die, chrome plated or black
- **Rubber bumper:** EPDM

Remarks

Weight: 510g.

1. rubber bumper

Hinged recessed handle, zinc die

	Product number	Locking	Surface	Opening angle	Installation type	Delivery Unit
a)	213-9101.00-00060	yes	chrome plated	60°	screw-on	10 pcs.
a)	213-9102.00-00060	yes	black	60°	screw-on	10 pcs.
a)	213-9101.00-00080	yes	chrome plated	80°	screw-on	10 pcs.
a)	213-9102.00-00080	yes	black	80°	screw-on	10 pcs.
b)	213-9001.00-00060	without	chrome plated	60°	screw-on	10 pcs.
b)	213-9002.00-00060	without	black	60°	screw-on	10 pcs.
b)	213-9001.00-00080	without	chrome plated	80°	screw-on	10 pcs.
b)	213-9002.00-00080	without	black	80°	screw-on	10 pcs.

