

2-, 3- and 4-Point Cam Adapter

2-151



Advantages

- 3-point cam adapter for cams of product system 1-102.
- With and without 90° stop.
- The raised rod stub is necessary for swinghandles, enabling the lower rod passing over the lower cap.
- 4-Point cam adapter: with additional linkage.
- For those applications, where beyond the standard control of 2 locking-rods, an additional rod can be used. E.g. controlling a switch or defeater-mechanism.



Material

- **3-point cam adapter and 4-point cam adapter:** zinc die, zinc plated

Remarks

Incl. 2 c-clips

Note: H-dimension of cam (C) increases by 4mm. E.g. cam 200-0418 results in an H-dimension of 22mm.

Please pay attention to the screw length: screw should enter at least 6mm.

1. with stop
2. without stop

Adapter for 3-point cam

	Product number	Stop	2-point locking	3-point locking	4-point locking	Installation type	Delivery Unit
a)	200-9595.00-00000	Yes	Yes	Yes	Yes	screw-on	1 pc.
b)	200-9596.00-00000	Yes	Yes	Yes	No	screw-on	1 pc.
c)	207-9595.00-00000	No	Yes	Yes	Yes	screw-on	1 pc.
d)	207-9596.00-00000	No	Yes	Yes	No	screw-on	1 pc.

