

Rod Latch for Internal Release

2-400.01



Advantages

- Rod latch for unlocking when swinghandle is closed.
- Door-thicknesses from 20 to 106mm.
- RH and LH version.
- 90° Opening angle.
- Rod connection threaded M8 or M10.

Material

- **Rod latch:** zinc die / steel, zinc plated

Remarks

1. stroke 20mm
2. cam-stroke 22mm
3. fastening of the dish by countersunk screws (custom made)

For swinghandle 130mm see 2-400.



Rod latch with rod connection threaded M10, version RH

	Product number	Door-thickness (S)	Installation type	Delivery Unit
a)	238-9101.00-00000	20 mm - 26 mm	screw-on	1 pc.
a)	238-9103.00-00000	27 mm - 33 mm	screw-on	1 pc.
a)	238-9105.00-00000	34 mm - 40 mm	screw-on	1 pc.
a)	238-9107.00-00000	70 mm - 76 mm	screw-on	1 pc.
a)	238-9109.00-00000	100 mm - 106 mm	screw-on	1 pc.

Rod latch with rod connection threaded M10, Version LH

	Product number	Door-thickness (S)	Installation type	Delivery Unit
b)	238-9102.00-00000	20 mm - 26 mm	screw-on	1 pc.

	Product number	Door-thickness (S)	Installation type	Delivery Unit
b)	238-9104.00-00000	27 mm - 33 mm	screw-on	1 pc.
b)	238-9106.00-00000	34 mm - 40 mm	screw-on	1 pc.
b)	238-9108.00-00000	70 mm - 76 mm	screw-on	1 pc.
b)	238-9110.00-00000	100 mm - 106 mm	screw-on	1 pc.

Rod latch with rod connection threaded M8, Version RH

	Product number	Door-thickness (S)	Installation type	Delivery Unit
a)	238-9301.00-00000	20 mm - 26 mm	screw-on	1 pc.
a)	238-9303.00-00000	27 mm - 33 mm	screw-on	1 pc.
a)	238-9305.00-00000	34 mm - 40 mm	screw-on	1 pc.
a)	238-9307.00-00000	70 mm - 76 mm	screw-on	1 pc.
a)	238-9309.00-00000	100 mm - 106 mm	screw-on	1 pc.

Rod latch with rod connection threaded M8, Version LH

	Product number	Door-thickness (S)	Installation type	Delivery Unit
b)	238-9302.00-00000	20 mm - 26 mm	screw-on	1 pc.
b)	238-9304.00-00000	27 mm - 33 mm	screw-on	1 pc.
b)	238-9306.00-00000	34 mm - 40 mm	screw-on	1 pc.
b)	238-9308.00-00000	70 mm - 76 mm	screw-on	1 pc.
b)	238-9310.00-00000	100 mm - 106 mm	screw-on	1 pc.

